

# CONNECTING BOX TYPE HA-VK 2



Photo: HA-VK 2 with cable glands HA-LSA 4A

## Features

- Compact connecting box for cable or conductor branching
- Total nine easily accessible slotted clamps, also acceptable for fine wires and two earth clamps
- Four lead-in parts available for plug-in Hamacher Quick-connectors
- On request also other types of cable glands available

## Technical Data

- |  |   |
|--|---|
| • Rated voltage max.   | 690 V   |
| • Rated current max.   | 47 A  |
| • Rated cross-section  | 10 mm <sup>2</sup>  |
| • Range of slotted clamps (clamped as single cable or fine wire) | - 2 x 10 mm <sup>2</sup> ; I <sub>n</sub> = 47 A<br>- 3 x 6 mm <sup>2</sup> ; I <sub>n</sub> = 36 A<br>- 4 x 4 mm <sup>2</sup> ; I <sub>n</sub> = 27 A<br>- 6 x 2,5 mm <sup>2</sup> ; I <sub>n</sub> = 20 A |
| • Ambient temperature  | -20 °C up to +40 °C   |
| • Weight   | 3,8 kg  |

## Types of protection

acc. to DIN EN 50014:2000 : I M2 EEx e I / II 2G EEx IIT4  
acc. to DIN EN 60529:2000 : at least IP 54

## Approval certification

IBExU01ATEX1073  
11.09.2001